



主要技术参数 (断路器用) MAIN TECHNICAL DATA (FOR CIRCUIT BREAKER)

额定电压 Rated voltage	126KV
额定电流 Rated current	4000,3150A
额定频率 Rated frequency	50/60HZ
额定短路开断电流 Rated short-circuit breaking current	40kA
额定短路开断电流开断次数 Operations of short-circuit breaking current interruption	30次
额定电流开断次数 Operations of rated current interruption	10,000次
最大直流分量 Max.DC-component	40%
额定短路关合电流 Rated short-circuit making current	100KA
额定峰值耐受电流 Rated peak withstand current	100KA
额定短时耐受电流(4秒) Rated short-time withstand current(4s)	40KA
短时(1min)工频耐受电压 Short-time(1min) power-frequency withstand voltage	*230KV
雷电冲击耐受电压(峰值) Lightning impulse withstand voltage(peak)	*550KV
额定触头压力下限时的回路电阻 Circuit resistance at minimum added force	≤ 15 μ Ω
机械寿命 Mechanical life	10000次
触头自闭力 Closing force due to bellows and atmosphere	600 ± 80N
额定开距下的触头反力 Force required to hold contacts open at full stroke	1000 ± 80N
触头允许磨损厚度 Contact erosion limit	3mm
贮存期 Shelf life	20年
质量/动触头质量 Total mass of interrupter/Moving mass of interrupter	61kg/16.8kg
额定操作顺序 Rated operating sequence	O-0.3s-CO-180s-CO

配套真空开关的机械参数(建议值)MECHANICAL DATA OF CIRCUIT-BREAKING RECOMMENDATIONS WITH THE INTERRUPTERS

触头开距 Rated contact stroke	45 ± 1mm
触头接触行程 Contact connection stroke	8 ± 2mm
平均分闸速度 (0-30mm行程) Average opening speed (0-30mm stroke)	3.5 ± 0.2m/s
平均合闸速度 (30mm-触头闭合) Average closing speed (30mm-contact making)	1.3 ± 0.2m/s
触头初压力 Added external contact force at contact touch point	≥ 3300N
额定触头压力 Added force on closed contacts	4800 ± 200N
触头合闸弹跳时间 Max.bouncing duration	≤ 5ms
触头分合闸不同期 Out of simultaneity of contact closing and opening	≤ 2ms
分闸触头反弹幅值 Max. rebound distance	≤ 2mm
分闸触头过冲幅值 Max. overtravel	≤ 2mm

备注 (Note) ;
* 须有外绝缘保护 (With insulation cover) ;